

SAMSON



RADIAL TRUCK TIRES

MID/LONG HAUL HIGHWAY ALL POSITION

GL 274A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 87440 | 8.25R20 | 14 | TT | S136/D134 | K | GL274A | 9.23 | 38.4 | 120 | S4940/D4675 | 6.5 | DG06C | 17.6 |
| 87450 | 9.00R20 | 16 | TT | S144/D142 | K | GL274A | 10.2 | 40.0 | 130 | S6175/D5840 | 7.0 | DG07C | 17.6 |
| 87460 | 10.00R20 | 16 | TT | S146/D143 | K | GL274A | 10.9 | 41.4 | 120 | S6610/D6005 | 7.5 | DG08C | 18.3 |
| 87462 | 10.00R20 | 18 | TT | S149/D146 | J | GL274A | 10.9 | 41.4 | 135 | S7160/D6610 | 7.5 | DG08C | 18.3 |
| 87470 | 11.00R20 | 16 | TT | S150/D147 | K | GL274A | 11.5 | 42.7 | 120 | S7390/D6780 | 8.0 | DG09C | 18.9 |
| 87472 | 11.00R20 | 18 | TT | S152/D149 | J | GL274A | 11.5 | 42.7 | 135 | S7830/D7160 | 8.0 | DG09C | 18.9 |
| TBA | 12.00R20 | 16 | TT | S152/D149 | K | GL274A | 12.4 | 44.5 | 110 | S7830/D7160 | 8.5 | DG09C | 20.2 |
| 87480 | 12.00R20 | 18 | TT | S154/D151 | K | GL274A | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 20.2 |
| 87400 | 9R22.5 | 14 | TL | S136/D134 | M | GL274A | 9.0 | 38.4 | 120 | S4940/D4675 | 6.6 | DR06 | 17.6 |
| 87404 | 10R22.5 | 14 | TL | S141/D139 | M | GL274A | 10.0 | 40.1 | 115 | S5675/D5355 | 7.5 | DR06 | 18.3 |
| TBA | 11R22.5 | 14 | TL | S144/D142 | M | GL274A | 10.9 | 41.5 | 105 | S6175/D5840 | 8.3 | DR07 | 18.3 |
| 87406 | 11R22.5 | 16 | TL | S146/D143 | M | GL274A | 10.9 | 41.5 | 120 | S6610/D6005 | 8.3 | DR07 | 18.3 |
| 87408 | 12R22.5 | 16 | TL | S150/D147 | M | GL274A | 11.8 | 42.7 | 120 | S7390/D6780 | 9.0 | DR08 | 19.5 |
| TBA | 12R22.5 | 18 | TL | S152/D149 | M | GL274A | 11.8 | 42.7 | 135 | S7830/D7160 | 9.0 | DR08 | 18.9 |

- Four "Z" shaped grooves designed to provide excellent slip resistance.
- Tread pattern optimized to resist irregular wear.
- Specialized tread compound designed for improved wear, resulting in lower cost per mile.

GL 276A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 87660 | 10.00R20 | 16 | TT | S146/D143 | K | GL276A | 10.94 | 41.4 | 120 | S6610/D6005 | 7.5 | DG08C | 18.3 |
| 87662 | 10.00R20 | 18 | TT | S149/D146 | J | GL276A | 10.94 | 41.4 | 135 | S7160/D6610 | 7.5 | DG08C | 18.3 |
| TBA | 11R22.5 | 14 | TL | S144/D142 | M | GL276A | 10.98 | 41.5 | 105 | S6175/D5840 | 8.3 | DR07 | 18.9 |
| 87606 | 11R22.5 | 16 | TL | S148/D144 | M | GL276A | 10.98 | 41.5 | 120 | S6610/D6005 | 8.3 | DR07 | 18.9 |

- Four-grooved tread design provides for superior stability at highway speeds and long, even tread wear.
- Specialized tread design allows for excellent slip resistance.
- Siping within ribs repels water for superior handling in varying road conditions.

GL 283A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-------------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 7.50R20 | 14 | TT | S130/D128 | K | GL283A | 8.5 | 36.8 | 120 | S4190/D3970 | 6.0 | DG06C | 17.6 |
| TBA | 8.25R20 | 14 | TT | S136/D134 | K | GL283A | 9.3 | 38.4 | 120 | S4940/D4675 | 6.5 | DG06C | TBA |
| TBA | 9.00R20 | TBA | TT | TBA | TBA | GL283A | 10.2 | 40.3 | TBA | TBA | TBA | TBA | TBA |
| TBA | 10.00R20 | TBA | TT | TBA | TBA | GL283A | 10.9 | 41.7 | TBA | TBA | TBA | TBA | TBA |
| TBA | 11.00R20 | 16 | TT | S150/D147 | K | GL283A | 11.5 | 42.9 | 120 | S7390/D6780 | 8.0 | DG09C | 20.2 |
| TBA | 11.00R20 | 18 | TT | S152/D149 | J | GL283A | 11.5 | 42.9 | 135 | S7830/D7160 | 8.0 | DG09C | 20.2 |
| TBA | 12.00R20 | 16 | TT | S152/D149 | K | GL283A | 12.4 | 44.5 | 110 | S7830/D7160 | 8.5 | DG09C | 20.8 |
| TBA | 12.00R20 | 18 | TT | S154/D151 | K | GL283A | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 20.8 |
| 88005 | 8R19.5 | 12 | TL | S124/D122 | L | GL283A | 7.9 | 33.8 | 110 | S3525/D3305 | 6.0 | CJ05 | 16.4 |
| 88008 | 215/75R17.5 | 12 | TL | S126/D124 | M | GL283A | 8.3 | 30.1 | 100 | S3750/D3525 | 6.00 | TL | 16.4 |
| 88000 | 215/75R17.5 | 16 | TL | S135/D133 | J | GL283A | 8.3 | 30.2 | 125 | S4805/D4540 | 6.00 | DR04 | 16.4 |
| 88010 | 235/75R17.5 | 14 | TL | S132/D130 | M | GL283A | 9.2 | 31.4 | 112 | S4410/D4190 | 6.8 | DR05 | 16.4 |
| 88011 | 235/75R17.5 | 16 | TL | S143/D141 | J | GL283A | 9.2 | 31.4 | 125 | S6005/D5675 | 6.8 | DR05 | 16.4 |
| TBA | 225/70R19.5 | 12 | TL | S125/D123 | M | GL283A | 8.9 | 31.9 | 95 | S3640/D3415 | 6.8 | DR06 | 16.4 |
| 88015 | 225/70R19.5 | 14 | TL | S128/D126 | L | GL283A | 8.9 | 31.9 | 110 | S3970/D3750 | 6.8 | DR06 | 16.4 |
| 88020 | 245/70R19.5 | 16 | TL | S136/D134 | M | GL283A | 9.8 | 33.0 | 119 | S4940/D4675 | 7.5 | DR06 | 16.4 |
| 88022 | 265/70R19.5 | 14 | TL | S137/D134 | M | GL283A | 10.3 | 34.1 | 110 | S5070/D4675 | 7.5 | DR06 | 16.4 |
| 88023 | 265/70R19.5 | 16 | TL | S140/D138 | M | GL283A | 10.3 | 34.1 | 112 | S5510/D5205 | 7.5 | TL | 16.4 |
| TBA | 265/70R19.5 | 18 | TL | S143/D141 | J | GL283A | 10.3 | 34.1 | 123 | S6005/D5675 | 7.5 | TL | 16.4 |
| 88025 | 255/70R22.5 | 16 | TL | S140/D137 | M | GL283A | 10.0 | 36.6 | 120 | S5510/D5070 | 7.5 | DR06 | 16.4 |
| 88027 | 275/70R22.5 | 18 | TL | S148/D145 | K | GL283A | 10.9 | 37.7 | 130 | S6940/D6395 | 8.3 | TL | 16.4 |
| TBA | 9R22.5 | 14 | TL | S136/D134 | M | GL283A | 9.0 | 38.4 | 120 | S4940/D4675 | 6.8 | DR06 | 18.3 |
| TBA | 10R22.5 | 14 | TL | S141/D139 | M | GL283A | 10.0 | 40.1 | 115 | S5675/D5355 | 7.5 | DR06 | 18.9 |
| TBA | 11R22.5 | 14 | TL | S144/D142 | M | GL283A | 10.9 | 41.5 | 105 | S6175/D5840 | 8.3 | DR07 | 18.9 |
| 88035 | 11R22.5 | 16 | TL | S146/D143 | M | GL283A | 10.9 | 41.4 | 120 | S6610/D6005 | 8.3 | DR07 | 18.9 |
| TBA | 12R22.5 | 16 | TL | S150/D147 | M | GL283A | 11.8 | 42.7 | 120 | S7390/D6780 | 9.0 | DR08 | 20.8 |

continued on next page →

GL 283A (continued)

| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-------------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 88040 | 11R24.5 | 14 | TL | S146/D143 | M | GL283A | 10.9 | 43.5 | 105 | S6610/D6005 | 8.3 | DR08 | 18.9 |
| 88042 | 11R24.5 | 16 | TL | S149/D146 | M | GL283A | 10.9 | 43.4 | 120 | S7160/D6610 | 8.3 | DR08 | 18.9 |
| 88045 | 295/75R22.5 | 14 | TL | S144/D141 | M | GL283A | 11.7 | 39.9 | 110 | S6175/D5675 | 9.0 | DR08 | 18.9 |
| TBA | 295/75R22.5 | 16 | TL | S146/D143 | M | GL283A | 11.7 | 40.1 | 120 | S6610/D6005 | 9.0 | DR08 | 18.9 |
| 88048 | 285/75R24.5 | 14 | TL | S144/D141 | M | GL283A | 11.1 | 41.3 | 110 | S6175/D5675 | 8.3 | DR07 | 18.9 |
| TBA | 285/75R24.5 | 16 | TL | S147/D144 | M | GL283A | 11.1 | 41.4 | 120 | S6780/D6175 | 8.3 | DR07 | 18.9 |

- Also for regional steer applications.
- Two-ply tread with heat resistant compound ensures suitability for long distance hauling.
- Tread compound designed for excellent wear, lowering the cost per mile.
- Specialized bead toe designed for improved durability.
- Self-cleaning grooves prevent stone retention.
- Groove design provides slip resistance.

GL 288A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 88865 | 10.00R20 | 16 | TT | S146/D143 | K | GL288A | 10.9 | 41.5 | 120 | S6610/D6005 | 7.5 | DG08C | 17.6 |
| 88866 | 10.00R20 | 18 | TT | S149/D146 | J | GL288A | 10.9 | 41.5 | 135 | S7160/D6610 | 7.5 | DG08C | 17.6 |
| 88868 | 11.00R20 | 16 | TT | S150/D147 | K | GL288A | 11.5 | 42.7 | 120 | S7390/D6780 | 8.0 | DG09C | 18.3 |
| 88870 | 11.00R20 | 18 | TT | S152/D149 | J | GL288A | 11.5 | 42.7 | 135 | S7830/D7160 | 8.0 | DG09C | 18.3 |
| TBA | 12.00R20 | 16 | TT | S152/D149 | K | GL288A | 12.4 | 44.5 | 110 | S7830/D7160 | 8.5 | DG09C | 18.9 |
| 88880 | 12.00R20 | 18 | TT | S154/D151 | K | GL288A | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 18.9 |
| TBA | 11R22.5 | 14 | TL | S144/D142 | M | GL288A | 10.9 | 40.9 | 105 | S6175/D5840 | 8.25 | DR07 | 17.0 |
| 88882 | 11R22.5 | 16 | TL | S148/D144 | M | GL288A | 10.9 | 40.9 | 120 | S6610/D6005 | 8.25 | DR07 | 17.0 |
| 88885 | 12R22.5 | 16 | TL | S150/D147 | M | GL288A | 11.8 | 42.7 | 120 | S7390/D6780 | 9.00 | DR08 | 18.3 |
| TBA | 13R22.5 | 18 | TL | S154/D151 | K | GL288A | 12.6 | 44.3 | 120 | S8270/D7610 | 9.75 | DR08 | TBA |

- Two-ply tread with heat resistant compound ensures suitability for long distance hauling.
- Tread compound and design provides excellent wear, reducing cost per mile.
- Specialized bead toe design for improved durability.
- Self-cleaning grooves reduce stone retention.
- Three "Z" shaped grooves provide excellent traction and braking.

GL 291A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 87250 | 12.00R24 | 18 | TT | S158/D155 | K | GL291A | 12.4 | 49.1 | 120 | S9370/D8540 | 8.5 | DG09C | 20.2 |
| TBA | 12.00R24 | 20 | TT | S160/D157 | J | GL291A | 12.4 | 49.1 | 130 | S9920/D9090 | 8.5 | DG09C | 20.2 |

- Three "Z" shaped grooves designed to provide excellent slip resistance.
- Special tread compound maximizes wear resistance.
- Tread pattern allows for uniform wear, excellent traction and dispersion of water.

GL 296A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-------------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 88030 | 295/80R22.5 | 16 | TL | S150/D147 | M | GL296A | 11.7 | 41.4 | 120 | S7390/D6780 | 9.0 | DR08 | 19.5 |
| 88032 | 315/80R22.5 | 18 | TL | S154/D151 | M | GL296A | 12.3 | 42.5 | 120 | S8270/D7610 | 9.0 | DR08 | 20.8 |
| 88033 | 315/80R22.5 | 20 | TL | S156/D150 | L | GL296A | 12.3 | 42.5 | 123 | S8820/D7390 | 9.0 | DR08 | 20.8 |

- Unique tread pattern with straight grooves and "S" shaped siping allows for excellent stability and handling under demanding conditions.

MID/LONG HAUL HIGHWAY DRIVE

GL 266D



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-------------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 86000 | 11R22.5 | 14 | TL | S144/D142 | M | GL266D | 10.9 | 42.2 | 105 | S6175/D5840 | 8.3 | DR07 | 32.1 |
| 86005 | 11R22.5 | 16 | TL | S146/D143 | M | GL266D | 10.9 | 42.2 | 120 | S6610/D6005 | 8.3 | DR07 | 32.1 |
| 86010 | 11R24.5 | 14 | TL | S146/D143 | M | GL266D | 10.9 | 44.3 | 105 | S6610/D6005 | 8.3 | DR08 | 32.1 |
| 86015 | 11R24.5 | 16 | TL | S149/D146 | M | GL266D | 10.9 | 44.3 | 120 | S7160/D6610 | 8.3 | DR08 | 32.1 |
| 86020 | 295/75R22.5 | 14 | TL | S144/D141 | M | GL266D | 11.7 | 40.9 | 110 | S6175/D5675 | 9.0 | DR08 | 32.1 |
| TBA | 295/75R22.5 | 16 | TL | S146/D143 | M | GL266D | 11.7 | 40.9 | 120 | S6610/D6005 | 9.0 | DR08 | 32.1 |
| 86025 | 285/75R24.5 | 14 | TL | S144/D141 | M | GL266D | 11.1 | 42.2 | 110 | S6175/D5675 | 8.3 | DR07 | 32.1 |
| TBA | 285/75R24.5 | 16 | TL | S147/D144 | M | GL266D | 11.1 | 42.2 | 120 | S6780/D6175 | 8.3 | DR07 | 32.1 |

- Premium closed shoulder design.
- Tread depths of up to 32/32" provide maximum traction and long service life, lowering cost per mile.
- Solid shoulder ribs distribute weight and torque evenly to prevent irregular wear.
- Siping creates better handling in wet road conditions.
- Stone ejecters help prevent retention of damaging stones.

GL 268D



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-------------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 11.00R20 | 16 | TT | S150/D147 | K | GL268D | 11.5 | 43.1 | 120 | S7390/D6780 | 8.0 | DG09C | 25.8 |
| TBA | 11.00R20 | 18 | TT | S152/D149 | J | GL268D | 11.5 | 43.1 | 135 | S7830/D7160 | 8.0 | DG09C | 25.8 |
| TBA | 12.00R20 | 16 | TT | S152/D149 | K | GL268D | 12.4 | 44.5 | 110 | S7830/D7160 | 8.5 | DG09C | 25.8 |
| TBA | 12.00R20 | 18 | TT | S154/D151 | K | GL268D | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 25.8 |
| 86050 | 11R22.5 | 14 | TL | S144/D142 | M | GL268D | 10.9 | 41.8 | 105 | S6175/D5840 | 8.3 | DR07 | 25.8 |
| 86055 | 11R22.5 | 16 | TL | S146/D143 | M | GL268D | 10.9 | 41.8 | 120 | S6610/D6005 | 8.3 | DR07 | 25.8 |
| TBA | 12R22.5 | 16 | TL | S150/D147 | M | GL268D | 11.8 | 42.7 | 120 | S7390/D6780 | 9.0 | DR08 | 25.8 |
| 86065 | 11R24.5 | 14 | TL | S146/D143 | M | GL268D | 10.9 | 43.9 | 105 | S6610/D6005 | 8.3 | DR08 | 25.8 |
| 86070 | 11R24.5 | 16 | TL | S149/D146 | M | GL268D | 10.9 | 43.9 | 120 | S7160/D6610 | 8.3 | DR08 | 25.8 |
| 86075 | 295/75R22.5 | 14 | TL | S144/D141 | M | GL268D | 11.7 | 40.6 | 110 | S6175/D5675 | 9.0 | DR08 | 25.8 |
| TBA | 295/75R22.5 | 16 | TL | S146/D143 | M | GL268D | 11.7 | 40.6 | 120 | S6610/D6005 | 9.0 | DR08 | 25.8 |
| 86080 | 295/80R22.5 | 16 | TL | S150/D147 | M | GL268D | 11.7 | 41.9 | 120 | S7390/D6780 | 9.0 | DR08 | 29.0 |
| 86085 | 285/75R24.5 | 14 | TL | S144/D141 | M | GL268D | 11.1 | 41.8 | 110 | S6175/D5675 | 8.3 | DR07 | 25.8 |
| TBA | 285/75R24.5 | 16 | TL | S147/D144 | M | GL268D | 11.1 | 41.8 | 120 | S6780/D6175 | 8.3 | DR07 | 25.8 |
| 86090 | 315/80R22.5 | 18 | TL | S154/D151 | M | GL268D | 12.3 | 43.0 | 120 | S8270/D7610 | 9.0 | DR08 | 29.0 |
| TBA | 315/80R22.5 | 20 | TL | S156/D150 | L | GL268D | 12.3 | 43.0 | 123 | S8820/D7390 | 9.0 | DR08 | 29.0 |

- Premium open shoulder design.
- Deep tread with siping allows for superior traction in varying road conditions.
- Solid lugs distribute weight and torque evenly to prevent irregular wear.

GL 275D



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 11R22.5 | 14 | TL | S144/D142 | M | GL275D | 10.9 | 41.5 | 105 | S6175/D5840 | 8.3 | DR07 | 21.4 |
| 87506 | 11R22.5 | 16 | TL | S148/D144 | M | GL275D | 10.9 | 41.7 | 120 | S6610/D6005 | 8.3 | DR07 | 21.4 |

- Thick, durable tread blocks provide excellent traction.
- Strong shoulder blocks connected to a reinforced rib design provides for excellent slip resistance.
- "Z" shaped center rib designed to prevent uneven wear and provide for long service life..

GL 293D



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 11.00R20 | 16 | TT | S150/D147 | K | GL293D | 11.5 | 43.1 | 120 | S7390/D6780 | 8.0 | DG09C | 25.8 |
| 87530 | 11.00R20 | 18 | TT | S152/D149 | J | GL293D | 11.5 | 43.1 | 135 | S7830/D7160 | 8.0 | DG09C | 25.8 |
| TBA | 12.00R20 | 16 | TT | S152/D149 | K | GL293D | 12.4 | 44.5 | 110 | S7830/D7160 | 8.5 | DG09C | 25.8 |
| 87535 | 12.00R20 | 18 | TT | S154/D151 | K | GL293D | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 25.8 |
| TBA | 11R22.5 | 14 | TL | S144/D142 | M | GL293D | 10.9 | 41.9 | 105 | S6175/D5840 | 8.25 | DR07 | TBA |
| TBA | 11R22.5 | 16 | TL | S146/D143 | M | GL293D | 10.9 | 41.9 | 120 | S6610/D6005 | 8.25 | DR07 | TBA |
| TBA | 11R24.5 | 14 | TL | S146/D143 | M | GL293D | 10.9 | 43.5 | 105 | S6610/D6005 | 8.25 | DR08 | TBA |
| TBA | 11R24.5 | 16 | TL | S149/D146 | M | GL293D | 10.9 | 43.4 | 120 | S7160/D6610 | 8.25 | DR08 | TBA |
| 86060 | 12R22.5 | 16 | TL | S150/D147 | M | GL293D | 11.8 | 43.1 | 120 | S7390/D6780 | 9.00 | DR08 | 25.8 |

- Two ply tread compound provides excellent wear characteristics.
- Specialized tread shape provides larger contact area and uniform wear.
- Unique tread pattern provides superb traction and braking.

MID/LONG HAUL HIGHWAY TRAILER SERVICE

GL 298T



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 12.00R20 | 16 | TT | S152/D149 | K | GL298T | 12.4 | 44.5 | 110 | S7830/D7160 | 8.5 | DG09C | 20.8 |
| 87540 | 12.00R20 | 18 | TT | S154/D151 | K | GL298T | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 20.8 |

- Wider, deeper tread allows for excellent wear and long service life.
- Shoulder lug grooves assist in providing excellent traction.
- Patented bead construction provides excellent load capability.
- Tread shape allows for uniform pressure distribution.
- Tread compound designed for rough road conditions.

GL 299T



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 11.00R20 | 16 | TT | S150/D147 | K | GL299T | 11.5 | 42.7 | 120 | S7390/D6780 | 8.0 | DG09C | 20.2 |
| 87545 | 11.00R20 | 18 | TT | S152/D149 | J | GL299T | 11.5 | 42.7 | 135 | S7830/D7160 | 8.0 | DG09C | 20.2 |

- Wider, deeper tread allows for excellent wear and long service life.
- Shoulder lug grooves assist in providing excellent traction.
- Patented bead construction provides excellent load capability.
- Tread shape allows for uniform pressure distribution.
- Tread compound designed for rough road conditions.

GL 285T



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-------------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 88105 | 11R22.5 | 14 | TL | S144/D142 | M | GL285T | 10.9 | 40.9 | 105 | S6175/D5840 | 8.3 | DR07 | 12.0 |
| TBA | 11R22.5 | 16 | TL | S146/D143 | M | GL285T | 10.9 | 40.9 | 120 | S6610/D6005 | 8.3 | DR07 | 12.0 |
| 88131 | 11R24.5 | 14 | TL | S146/D143 | M | GL285T | 10.9 | 43.1 | 105 | S6610/D6005 | 8.3 | DR08 | 12.0 |
| 88130 | 11R24.5 | 16 | TL | S149/D146 | M | GL285T | 10.9 | 43.1 | 120 | S7160/D6610 | 8.3 | DR08 | 12.0 |
| 88125 | 295/75R22.5 | 14 | TL | S144/D141 | M | GL285T | 11.7 | 39.7 | 110 | S6175/D5675 | 9.0 | DR08 | 12.0 |
| 88120 | 295/75R22.5 | 16 | TL | S146/D143 | M | GL285T | 11.7 | 39.7 | 120 | S6610/D6005 | 9.0 | DR08 | 12.0 |
| 88102 | 285/75R24.5 | 14 | TL | S144/D141 | M | GL285T | 11.14 | 40.9 | 110 | S6175/D5675 | 8.3 | DR07 | 12.0 |
| 88100 | 285/75R24.5 | 16 | TL | S147/D144 | M | GL285T | 11.14 | 40.9 | 120 | S6780/D6175 | 8.3 | DR07 | 12.0 |

- Specialized tread compound designed for superb wear at highway speeds.
- Tread pattern provides for excellent drainage and slip resistance.
- Grooves within tread reduce irregular wear and improve stability.

GL 286T



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-------------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 88200 | 385/65R22.5 | 18 | TL | 158 | L | GL286T | 15.31 | 42.20 | 120 | 9370 | 11.75 | TL | 19.5 |
| TBA | 425/65R22.5 | 20 | TL | 164 | K | GL286T | 16.61 | 44.17 | 120 | 11000 | 12.25 | TL | 20.8 |

- Specialized tread compound designed for excellent wear at highway speeds.
- Tread pattern provides for superior drainage and slip resistance.
- Fine grooves ensure regular wear and improve stability.

MID/SHORT HAUL MIXED ROAD ALL POSITION

GL 665A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-------------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 11R22.5 | 14 | TL | S144/D142 | M | GL665A | 10.9 | 42.2 | 105 | S6175/D5840 | 8.3 | DR07 | 21.4 |
| 87001 | 11R22.5 | 16 | TL | S146/D143 | M | GL665A | 10.9 | 42.2 | 120 | S6610/D6005 | 8.3 | DR07 | 21.4 |
| 87002 | 12R22.5 | 16 | TL | S150/D147 | M | GL665A | 11.8 | 42.7 | 120 | S7390/D6780 | 9.0 | DR08 | 22.0 |
| 87003 | 13R22.5 | 18 | TL | S154/D151 | K | GL665A | 12.6 | 44.3 | 120 | S8270/D7610 | 9.8 | DR08 | 22.0 |
| 87004 | 295/80R22.5 | 16 | TL | S150/D147 | M | GL665A | 11.7 | 41.5 | 120 | S7390/D6780 | 9.0 | DR08 | 22.0 |
| 87005 | 315/80R22.5 | 18 | TL | S154/D151 | L | GL665A | 12.3 | 42.6 | 120 | S8270/D7610 | 9.0 | DR08 | 22.7 |
| TBA | 315/80R22.5 | 20 | TL | S156/D150 | K | GL665A | 12.3 | 42.6 | 123 | S8820/D7390 | 9.0 | DR08 | 22.7 |

- Specialized "Z" shaped grooves provide for excellent traction and braking abilities.
- Compound is specifically designed to ensure tear-resistance.
- Lug grooves located on the shoulders improve traction capability.

GL 671A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 6.50R16 | 12 | TT | S110/D105 | L | GL671A | 7.3 | 29.5 | 97 | S2340/D2040 | 5.5F | CJ01 | 13.2 |
| TBA | 7.00R16 | 14 | TT | S118/D114 | L | GL671A | 7.9 | 30.5 | 111 | S2900/D2600 | 5.5F | DG04C | 13.9 |
| 87105 | 7.50R16 | 14 | TT | S122/D118 | L | GL671A | 8.5 | 31.7 | 111 | S3305/D2900 | 6.0G | DG04C | 13.9 |
| 87120 | 8.25R16 | 14 | TT | S126/D122 | L | GL671A | 9.3 | 33.7 | 97 | S3745/D3305 | 6.5H | DG05C | 15.1 |
| 87130 | 7.50R20 | 14 | TT | S130/D128 | K | GL671A | 8.5 | 36.8 | 120 | S4190/D3970 | 6.0 | DG06C | 16.4 |
| 87140 | 8.25R20 | 14 | TT | S136/D134 | K | GL671A | 9.3 | 38.4 | 120 | S4940/D4675 | 6.5 | DG06C | 17.6 |
| 87150 | 9.00R20 | 16 | TT | S144/D142 | K | GL671A | 10.2 | 40.1 | 130 | S6175/D5840 | 7.0 | DG07C | 18.9 |
| 87160 | 10.00R20 | 16 | TT | S146/D143 | K | GL671A | 10.9 | 41.5 | 120 | S6610/D6005 | 7.5 | DG08C | 20.2 |
| 87162 | 10.00R20 | 18 | TT | S149/D146 | J | GL671A | 10.9 | 41.5 | 135 | S7160/D6610 | 7.5 | DG08C | 20.2 |
| 87170 | 11.00R20 | 16 | TT | S150/D147 | K | GL671A | 11.5 | 42.7 | 120 | S7390/D6780 | 8.0 | DG09C | 20.8 |
| 87172 | 11.00R20 | 18 | TT | S152/D149 | J | GL671A | 11.5 | 42.7 | 135 | S7830/D7160 | 8.0 | DG09C | 20.8 |
| 87173 | 12.00R20 | 18 | TT | S154/D151 | K | GL671A | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 21.4 |
| TBA | 11R22.5 | 14 | TL | S144/D142 | M | GL671A | 10.9 | 41.5 | 105 | S6175/D5840 | 8.3 | DR07 | 20.2 |
| 87175 | 11R22.5 | 16 | TL | S146/D143 | M | GL671A | 10.9 | 41.5 | 120 | S6610/D6005 | 8.3 | DR07 | 20.2 |
| TBA | 11R24.5 | 14 | TL | S146/D143 | M | GL671A | 10.9 | 43.5 | 105 | S6610/D6005 | 8.3 | DR08 | 20.8 |
| 87188 | 11R24.5 | 16 | TL | S149/D146 | M | GL671A | 10.9 | 43.5 | 120 | S7160/D6610 | 8.3 | DR08 | 20.8 |
| 87180 | 12R22.5 | 16 | TL | S150/D147 | M | GL671A | 11.8 | 42.7 | 120 | S7390/D6780 | 9.0 | DR08 | 20.8 |
| 87185 | 13R22.5 | 18 | TL | S154/D151 | K | GL671A | 12.6 | 44.3 | 120 | S8270/D7610 | 9.8 | DR08 | 21.4 |

- Three "Z" shaped grooves designed to provide excellent traction and braking ability.
- Designed with special tear resistant compound.
- Shoulder lug grooves designed to aid in excellent traction.

GL 679A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 87910 | 7.50R16 | 14 | TT | S122/D118 | L | GL679A | 8.5 | 31.7 | 111 | S3305/D2900 | 6.0G | DG04C | 14.5 |
| 87920 | 8.25R16 | 14 | TT | S126/D122 | L | GL679A | 9.5 | 33.7 | 97 | S3745/D3305 | 6.5H | DG05C | 15.1 |

- For mid/long haul light trucks.
- Specialized tread compound allows for improved wear at highway speeds.
- Unique groove pattern is designed to provide excellent handling and traction.
- Lug grooves on tread blocks improve slip resistance and reduce uneven wear.

GL 689A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-------------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 88380 | 9.00R20 | 16 | TT | S144/D142 | K | GL689A | 10.2 | 40. | 130 | S6175/D5840 | 7.0 | DG07C | 21.4 |
| TBA | 10.00R20 | 16 | TT | S146/D143 | K | GL689A | 10.8 | 41.5 | 120 | S6610/D6005 | 7.5 | DG08C | 22.0 |
| 88385 | 10.00R20 | 18 | TT | S149/D146 | J | GL689A | 10.9 | 41.5 | 135 | S7160/D6610 | 7.5 | DG08C | 22.0 |
| TBA | 11.00R20 | 16 | TT | S150/D147 | K | GL689A | 11.5 | 42.8 | 120 | S7390/D6780 | 8.0 | DG09C | 22.7 |
| 88390 | 11.00R20 | 18 | TT | S152/D149 | J | GL689A | 11.5 | 42.8 | 135 | S7830/D7160 | 8.0 | DG09C | 22.7 |
| 88395 | 12.00R20 | 18 | TT | S154/D151 | K | GL689A | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 23.3 |
| TBA | 385/65R22.5 | TBA | TL | TBA | TBA | GL689A | TBA | TBA | TBA | TBA | TBA | TBA | TBA |

- Specialized "Z" shaped grooves provide for excellent traction and braking abilities.
- Compound is specifically designed to ensure tear-resistance.
- The deep-grooved tread pattern allows for long service life.

MID/SHORT HAUL MIXED ROAD DRIVE

GL 663D



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 7.00R16 | 14 | TT | S118/D114 | L | GL663D | 7.9 | 30.8 | 111 | S2900/D2600 | 5.5F | DG04C | 18.9 |
| TBA | 7.50R16 | 14 | TT | S122/D118 | L | GL663D | 8.5 | 31.9 | 111 | S3305/D2900 | 6.0G | DG04C | 19.5 |
| TBA | 8.25R16 | 14 | TT | S126/D122 | L | GL663D | 9.3 | 33.8 | 97 | S3745/D3305 | 6.5H | DG05C | 20.2 |
| TBA | 8.25R20 | 14 | TT | S136/D134 | K | GL663D | 9.3 | 38.2 | 120 | S4940/D4675 | 6.5 | DG06C | 20.8 |
| TBA | 9.00R20 | 16 | TT | S144/D142 | K | GL663D | 10.2 | 40.1 | 130 | S6175/D5840 | 7.0 | DG07C | 23.3 |
| TBA | 11.00R20 | 16 | TT | S150/D147 | K | GL663D | 11.6 | 42.9 | 120 | S7390/D6780 | 8.0 | DG09C | 24.6 |
| TBA | 11.00R20 | 18 | TT | S152/D149 | J | GL663D | 11.6 | 42.9 | 135 | S7830/D7160 | 8.0 | DG09C | 24.6 |
| TBA | 12.00R20 | 18 | TT | S154/D151 | K | GL663D | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 24.6 |

- Durable, defined grooves provide for excellent traction.
- Unique, deep tread pattern is designed for long service life.
- Siping within tread blocks help ensure uniform wear and excellent stability.

GL 672D



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 7.00R16 | 14 | TT | S118/D114 | L | GL672D | 7.9 | 30.7 | 111 | S2900/D2600 | 5.5F | DG04C | 17.6 |
| TBA | 7.50R16 | 14 | TT | S122/D118 | L | GL672D | 8.5 | 31.7 | 111 | S3305/D2900 | 6.0G | DG04C | 18.3 |
| TBA | 8.25R16 | 14 | TT | S126/D122 | L | GL672D | 9.3 | 33.7 | 97 | S3745/D3305 | 6.5H | DG05C | 18.9 |
| TBA | 8.25R20 | 14 | TT | S136/D134 | K | GL672D | 9.1 | 38.0 | 120 | S4940/D4675 | 6.5 | DG06C | 18.9 |
| 87220 | 9.00R20 | 16 | TT | S144/D142 | K | GL672D | 10.2 | 40.1 | 130 | S6175/D5840 | 7.0 | DG07C | 19.5 |
| 87225 | 10.00R20 | 16 | TT | S146/D143 | K | GL672D | 10.9 | 41.5 | 120 | S6610/D6005 | 7.5 | DG08C | 20.8 |
| 87230 | 10.00R20 | 18 | TT | S149/D146 | J | GL672D | 10.9 | 41.5 | 135 | S7160/D6610 | 7.5 | DG08C | 20.8 |
| 87235 | 11.00R20 | 16 | TT | S150/D147 | K | GL672D | 11.5 | 42.7 | 120 | S7390/D6780 | 8.0 | DG09C | 21.4 |
| 87240 | 11.00R20 | 18 | TT | S152/D149 | J | GL672D | 11.5 | 42.7 | 135 | S7830/D7160 | 8.0 | DG09C | 21.4 |

- Specialized "Z" shaped thick center rib and wide lug grooves provide excellent resistance to slipping.
- Reinforced lug blocks of shoulder sidewall provide excellent traction.
- Tread angles designed for improved cut & tear resistance.
- Tread design has inherent self cleaning characteristics.

GL 681D



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 88400 | 9.00R20 | 16 | TT | S144/D142 | K | GL681D | 10.2 | 40.3 | 130 | \$6175/D5840 | 7.0 | DG07C | 21.4 |
| TBA | 10.00R20 | 16 | TT | S146/D143 | K | GL681D | 10.9 | 41.7 | 120 | \$6610/D6005 | 7.5 | DG08C | 22.7 |
| 88405 | 10.00R20 | 18 | TT | S149/D146 | J | GL681D | 10.9 | 41.7 | 135 | \$7160/D6610 | 7.5 | DG08C | 22.7 |
| TBA | 11.00R20 | 16 | TT | S150/D147 | K | GL681D | 11.5 | 42.9 | 120 | \$7390/D6780 | 8.0 | DG09C | 23.3 |
| 88410 | 11.00R20 | 18 | TT | S152/D149 | J | GL681D | 11.5 | 42.9 | 135 | \$7830/D7160 | 8.0 | DG09C | 23.3 |
| 88415 | 12.00R20 | 18 | TT | S154/D151 | K | GL681D | 12.4 | 44.5 | 120 | \$8270/D7610 | 8.5 | DG09C | 23.9 |

- Thick, durable block and lug grooves provide for excellent traction.
- Designed for even distribution where the tread meets the surface.
- Tread pattern provides for slip resistance, prevents irregular wear, and improves stability.

MID/SHORT HAUL CONSTRUCTION SERVICE ALL POSITION

GL 678D



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 9.00R20 | 16 | TT | S144/D142 | K | GL678A | 10.2 | 40.2 | 130 | \$6175/D5840 | 7.0 | DG07C | 20.2 |
| 87860 | 10.00R20 | 16 | TT | S146/D143 | K | GL678A | 10.9 | 41.7 | 120 | \$6610/D6005 | 7.5 | DG08C | 22.7 |
| 87862 | 10.00R20 | 18 | TT | S149/D146 | J | GL678A | 10.9 | 41.7 | 135 | \$7160/D6610 | 7.5 | DG08C | 22.7 |
| 87865 | 11.00R20 | 16 | TT | S150/D147 | K | GL678A | 11.5 | 42.9 | 120 | \$7390/D6780 | 8.0 | DG09C | 23.3 |
| 87870 | 11.00R20 | 18 | TT | S152/D149 | J | GL678A | 11.5 | 42.9 | 135 | \$7830/D7160 | 8.0 | DG09C | 23.3 |
| TBA | 11R22.5 | 16 | TL | S146/D143 | M | GL678A | 10.9 | 41.8 | 120 | \$6610/D6005 | 8.3 | DR07 | 22.7 |
| TBA | 12R22.5 | 16 | TL | S150/D147 | M | GL678A | 11.8 | 42.7 | 120 | \$7390/D6780 | 9.0 | DR08 | 23.3 |
| TBA | 12R22.5 | 18 | TL | S152/D149 | M | GL678A | 11.8 | 42.7 | 135 | \$7830/D7160 | 9.0 | DR08 | 23.3 |

- Specialized 3 groove design prevents irregular wear and provides excellent stability.
- Thick, durable tread blocks provide excellent traction.
- Unique groove pattern is designed to resist stone retention and has an inherent self-cleaning property.
- Tread depth allows for long service life, lowering the cost per mile.

MID/SHORT HAUL CONSTRUCTION SERVICE DRIVE

GL 687D



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-------------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 11.00R20 | 16 | TT | S150/D147 | K | GL687D | 11.5 | 42.9 | 120 | \$7390/D6780 | 8.0 | DG09C | 24.6 |
| 88340 | 11.00R20 | 18 | TT | S152/D149 | J | GL687D | 11.5 | 42.9 | 135 | \$7830/D7160 | 8.0 | DG09C | 24.6 |
| TBA | 12.00R20 | 18 | TT | S154/D151 | K | GL687D | 12.4 | 44.5 | 120 | \$8270/D7610 | 8.5 | DG09C | 24.6 |
| 88355 | 12R22.5 | 16 | TL | S150/D147 | M | GL687D | 11.8 | 42.9 | 120 | \$7390/D6780 | 9.0 | DR08 | 24.6 |
| 88370 | 315/80R22.5 | 18 | TL | S154/D151 | L | GL687D | 12.3 | 42.9 | 120 | \$8270/D7610 | 9.0 | DR08 | 26.5 |
| TBA | 315/80R22.5 | 20 | TL | S156/D150 | K | GL687D | 12.3 | 42.4 | 123 | \$8820/D7390 | 9.0 | TL | 26.5 |

- Directional tread pattern and thick, durable tread blocks for improved traction.
- Tread depth allows for increased service life, reducing cost per mile.
- Wide footprint for excellent stability.

MID/SHORT HAUL MINING ALL POSITION

GL 908A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 11.00R20 | 18 | TT | S152/D149 | J | GL908A | 11.7 | 43.6 | 135 | \$7830/D7160 | 8.0 | DG09C | 31.5 |
| TBA | 12.00R20 | 18 | TT | S154/D151 | TBA | GL908A | 12.4 | 44.5 | 120 | \$8270/D7610 | 8.5 | DG09C | TBA |

- All position, short-haul tire for construction and mining sites.
- Specialized pattern designed to navigate rough and rocky surfaces.
- Tread compound engineered for resistance to cuts, chips, tearing and irregular wear.
- Thick, strong tread blocks provide superb traction capabilities.
- Wide tread surface for excellent stability.
- Deep tread allows for long service life.

GL 909A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | TBA | TBA | TBA | TBA | TBA | TBA | TBA | TBA | TBA | TBA | TBA | TBA | TBA |

- **Designed for use as an all-position tire in moderate to severe applications.**
- **Extra-deep groove design for increased mileage.**
- **Robust center blocks and optimized lateral grooves ensure superior traction and braking performance even under the most demanding circumstances.**
- **Wide tread stance provides excellent stability.**
- **Tread compound designed for chip and tear resistance, and also provides reduced heat build-up resulting in longer service life.**

GL 969A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 9.00R20 | 16 | TT | S144/D142 | K | GL969A | 10.2 | 40.4 | 130 | S6175/D5840 | 7.0 | DG07C | 23.3 |
| TBA | 10.00R20 | 16 | TT | S146/D143 | K | GL969A | 10.9 | 41.7 | 120 | S6610/D6005 | 7.5 | DG08C | 23.9 |
| TBA | 10.00R20 | 18 | TT | S149/D146 | J | GL969A | 10.9 | 41.7 | 135 | S7160/D6610 | 7.5 | DG08C | 23.9 |
| TBA | 11.00R20 | 16 | TT | S150/D147 | K | GL969A | 11.5 | 42.9 | 120 | S7390/D6780 | 8.0 | DG09C | 24.6 |
| TBA | 11.00R20 | 18 | TT | S152/D149 | J | GL969A | 11.5 | 42.9 | 135 | S7830/D7160 | 8.0 | DG09C | 24.6 |
| TBA | 12.00R20 | 18 | TT | S154/D151 | K | GL969A | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 25.2 |

- **Aggressive lugs provide for a powerful grip on or off road.**
- **Specialized pattern is designed for severe service applications.**
- **Compounded for excellent resistance to cuts and chips, and to fight irregular wear.**
- **Wide tread design allows for more surface contact and improved stability.**

GL 992A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 88910 | 10.00R20 | 16 | TT | S146/D143 | K | GL992A | 10.9 | 41.7 | 120 | S6610/D6005 | 7.5 | DG08C | 23.9 |
| 88912 | 10.00R20 | 18 | TT | S149/D146 | J | GL992A | 10.9 | 41.7 | 135 | S7160/D6610 | 7.5 | DG08C | 23.9 |
| 88915 | 11.00R20 | 16 | TT | S150/D147 | K | GL992A | 11.5 | 42.7 | 120 | S7390/D6780 | 8.0 | DG09C | 24.6 |
| 88918 | 11.00R20 | 18 | TT | S152/D149 | J | GL992A | 11.5 | 42.7 | 135 | S7830/D7160 | 8.0 | DG09C | 24.6 |
| 88920 | 12.00R20 | 18 | TT | S154/D151 | K | GL992A | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 25.2 |
| TBA | 11R22.5 | 14 | TL | S144/D142 | M | GL992A | 10.9 | 41.9 | 105 | S6175/D5840 | 8.3 | DR07 | 23.9 |
| 88900 | 11R22.5 | 16 | TL | S146/D143 | M | GL992A | 10.9 | 41.9 | 120 | S6610/D6005 | 8.3 | DR07 | 23.9 |
| 88925 | 12R22.5 | 16 | TL | S150/D147 | M | GL992A | 11.8 | 42.7 | 120 | S7390/D6780 | 9.0 | DR08 | 24.6 |
| 88905 | 13R22.5 | 18 | TL | S154/D151 | K | GL992A | 12.6 | 44.3 | 120 | S8270/D7610 | 9.8 | DR08 | 24.6 |

- **Applicable for mining, logging, and construction sites.**
- **Specialized tread pattern for use in severe conditions.**
- **New cut resistant compound.**
- **Thick, strong blocks provide for excellent traction.**
- **Wide footprint for excellent stability.**

OFF ROAD ALL POSITION

GL 073A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| 87380 | 12.00R20 | 18 | TT | S154/D151 | K | GL073A | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 22.7 |
| TBA | 12.00R20 | 18 | TL | S154/D151 | K | GL073A | 12.4 | 44.5 | 120 | S8270/D7610 | 8.5 | DG09C | 22.7 |
| TBA | 12.00R20 | 20 | TT | S156/D153 | J | GL073A | 12.4 | 44.5 | 130 | S8820/D8050 | 8.5 | DG09C | 22.7 |
| TBA | 14.00R20 | 18 | TT | S161/D158 | J | GL073A | 14.8 | 48.8 | 100 | S10200/D9370 | 10.0 | DG09C | 25.2 |
| 87303 | 14.00R20 | 18 | TL | S161/D158 | J | GL073A | 14.8 | 48.8 | 100 | S10200/D9370 | 10.0 | DG09C | 25.2 |
| TBA | 14.00R20 | 20 | TT | S164/D161 | G | GL073A | 14.8 | 48.8 | 115 | S11000/D10200 | 10.0 | DG09C | 25.2 |
| 87305 | 14.00R20 | 20 | TL | S164/D161 | G | GL073A | 14.8 | 48.8 | 115 | S11000/D10200 | 10.0 | DG09C | 25.2 |
| TBA | 15.5R20 | 18 | TL | TBA | G | GL073A | 17.3 | 50.0 | 115 | 13230 | 11.3 | TBA | TBA |
| TBA | 15.5R20 | 20 | TL | TBA | G | GL073A | 17.3 | 50.0 | 130 | 14350 | 11.3 | TBA | TBA |
| 87310 | 16.00R20 | 18 | TL | 173 | G | GL073A | 16.7 | 51.7 | 115 | 14350 | 11.3 | TL | 25.2 |
| 87315 | 395/85R20 | 14 | TL | 158 | K | GL073A | 15.4 | 46.7 | 95 | 9370 | 11.0 | TL | 31.5 |
| TBA | 395/85R20 | 16 | TL | 162 | J | GL073A | 15.4 | 46.7 | 115 | 10470 | 11.0 | TL | 31.5 |

- Applicable for use on soil, sand, and grassy conditions.
- Strong tread block connected by reinforced ribs provides superb durability.
- Rounded shoulder design for excellent off-road capabilities.
- Raised sidewall rib protects against sidewall damage.

ALL POSITION BUS

GL 828A



| Base Item No. | Tire Size | P.R. | Type | Load Index | Speed Symbol | Pattern | Section Width (in.) | Overall Diam. (in.) | Infl. (psi) | Max. Load (lbs.) | Standard Rim | Tire Valve | T.D. (32nds) |
|---------------|-----------|------|------|------------|--------------|---------|---------------------|---------------------|-------------|------------------|--------------|------------|--------------|
| TBA | 11R22.5 | 14 | TL | S144/D142 | J | GL828A | 10.9 | 41.7 | 105 | S6175/D5840 | 7.5 | DR07 | 25.2 |
| TBA | 11R22.5 | 16 | TL | S146/D143 | J | GL828A | 10.9 | 41.7 | 120 | S6610/D6005 | 7.5 | DR07 | 25.2 |

- Excellent all position tire for metropolitan bus applications.
- Specialized tread compound design for improved wear.
- Extra-deep groove design for increased mileage.
- Optimized tread grooves for excellent water dispersion and slip-resistance.
- Strong sidewall provides superior protection against curb damage.
- Reinforced bead for excellent load carrying capabilities.
- Self-cleaning grooves and thick tread compound resist punctures.

PATTERN DESIGNATIONS



MTR PATTERN DESIGNATIONS

Example: GL 266D

- All radial truck tires begin with "GL"
- Followed by one number
- Followed by a 2-digit GTC pattern code
- Followed by one letter

| # | Application |
|---|--------------------------------------|
| 0 | Special Application |
| 1 | Long Haul Highway |
| 2 | Mid/Long Haul Highway |
| 6 | Mid/Short Haul Mixed Road |
| 8 | Bus Service |
| 9 | Severe Service (Mining Construction) |

| Letter | Position |
|--------|------------------|
| A | All Position |
| D | Drive Position |
| T | Trailer Position |
| F | Steer Position |

Radial Truck Tire LIMITED WARRANTY

Limited Warranty

GreatLakes Tire Company hereby warrants every new Samson/Advance radial truck tire is free from defects in workmanship and material for the life of the original tread of a new tire less 2/32". The life of the original usable tread ends when the tire tread has only 2/32" remaining.

50% Free Replacement Warranty

If a defect in workmanship and materials is found in any Samson/Advance radial truck tire within the first 50% of tread wear (calculated by subtracting one-half (1/2) the difference between the original new tire depth and 2/32" from the original new tire tread depth), GreatLakes Tire Company will refund the cost of a replacement. 50% free replacement applies to first class new tires only as follows:

1. The defective Samson/Advance radial truck tire must be replaced with a comparable new Samson/Advance radial truck tire by an authorized Samson/Advance dealer. Proof of replacement will be required.
2. Applicable taxes on the new tires shall be paid by the owner.
3. All cost for mounting and balancing will be paid by the owner.
4. 50% free replacement applies to new first class tires only. Blems, retreads and road hazard tires are specifically excluded.

General Warranty

If a defect in workmanship and materials is found in any Samson/Advance radial truck tire after the first 50% of tread wear (see definition above) the tire will be pro-rated down to 2/32" of the original tread. Applicable taxes on the new tire and costs of mounting and balancing service will be paid by the owner. Adjustment on out-of-round tires is allowed only during the first 2/32" of the original tread.

Casing Warranty

A. Casings of Samson/Advance truck tires are warranted against defects in workmanship and materials through the life of the second retread. The life of the 2nd retread is considered to end when the remaining tread on the second retread reaches a buffing stage of 2/32" or less.

B. If an examination shows that a casing of a Samson/Advance radial truck tire failed to such a defect, GreatLakes Tire Company will give a credit toward the purchase price of a comparable new Samson/Advance tire in amount indicated below:

| SIZE | CASING ALLOWANCE |
|-----------------------------------|------------------|
| 215/75R17.5, 235/75R17.5 | \$10.00 |
| 8R19.5 | \$20.00 |
| 225/70R19.5, 245/70R19.5, 9R22.5 | \$30.00 |
| 10R22.5, 255/70R22.5, 275/70R22.5 | \$50.00 |
| 11R22.5, 295/75R22.5 | \$60.00 |
| 11R24.5, 285/75R24.5 | \$60.00 |
| 12R22.5 | \$70.00 |
| 315/80R22.5 | \$80.00 |
| 385, 425/65R22.5 | \$80.00 |

C. Above casing warranty is valid only for five (5) years after date of manufacture of original tire.

Exclusions

A. All Samson/Advance warranties are limited to the original purchaser and the original vehicle on which they are mounted and are not transferable to subsequent purchasers or vehicles.

B. This limited warranty is applicable only in the United States and Canada. Any tires used or equipped on vehicles registered or operated outside of the United States or Canada are not eligible for this warranty.

C. The following will not be covered by the Limited Warranty

1. Tire branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem) or previously adjusted.
2. Failure, damage or irregular wear due to:
 - a. Road hazards (i.e. puncture, cut, snag, impact breaks, etc.), wreck, collision;
 - b. Fire, accident or vandalism, improper alignment, wheel imbalance, faulty shocks or brakes;
 - c. Mechanical condition of vehicle, including misalignment, wheel imbalance, faulty shocks or brakes;
 - d. Misapplication of tire, use of improper inner tube;
 - e. Any alteration of the tire or addition of alien material or transfer from one vehicle to another;
 - f. Radial truck tire failed due to faulty retreading or materials.
3. Cost of mounting and balancing service, loss of time, inconvenience or any incidental or consequential damages is not covered.

Owner's Obligations

In order for tires to be eligible for this Limited Warranty, the owner must:

- A.** Present the defective tire to an authorized Samson/Advance dealer from which the original purchase was made.
- B.** Present proof of purchase to the satisfaction of the dealer.
- C.** Properly fill out and sign a Samson/Advance Warranty Claim Form.
- D.** Pay the amount due on a new tire, less the amount of credit.

Disclaimer

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of Advance/Samson tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.



Distributed By
GreatLakes Tire Company
 4580 Stephen Circle NW
 Suite 202
 Canton, Ohio 44718
 Phone: 330-498-5000
 Fax: 330-498-5002
 E-mail: sales@gtcna.com

SAMSON

RADIAL TRUCK TIRES



4580 Stephen Circle NW
Suite 202
Canton, Ohio 44718
Phone: 330-498-5000
Fax: 330-498-5002
E-mail: sales@gtcna.com