

# SAMSON

**FARM BACKHOE SKIDSTEER**



Distributed by:



**GREAT LAKES**  
**TIRE COMPANY**

3425 Alabama Avenue NW • PO Box 210 • North Lawrence, Ohio 44666  
Phone: 330-837-1700 • Fax: 330-837-1701 • E-mail: [sales@ted-inc.com](mailto:sales@ted-inc.com)

## Backhoe Rear- Industrial Plus R-4 XHD



(R-4A model shown)

| Catalog No. | Size/Ply    | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|-------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 99060H-2    | 14.9L-24/12 | TBLS | R-4A    | A8           | 14.9                | 48.9                   | 42                       | 6395           | 32.0                |
| 99010L-2    | 16.9L-24/12 | TBLS | R-4A    | A8           | 16.9                | 51.5                   | 38                       | 7165           | 32.0                |
| 99010H-2    | 16.9L-24/12 | TBLS | R-4A    | A8           | 16.9                | 51.5                   | 38                       | 7165           | 32.0                |
| 99020L-2    | 17.5L-24/12 | TBLS | R-4A    | A8           | 17.5                | 48.9                   | 38                       | 6605           | 32.0                |
| 99020H-2    | 17.5L-24/12 | TBLS | R-4A    | A8           | 17.5                | 48.9                   | 38                       | 6605           | 32.0                |
| 99030H-2    | 19.5L-24/14 | TBLS | R-4A    | A8           | 19.5                | 51.7                   | 38                       | 8145           | 35.9                |
| 99040H-2    | 21L-24/16   | TBLS | R-4A    | A8           | 21.0                | 54.3                   | 41                       | 9920           | 40.1                |

### Tire Features & Benefits

- Ultimate backhoe tire.
- Extra wide tread design for high flotation and super stability in extreme conditions.
- Large center bars for superior road-ability, extra deep tread for superior traction.
- Reinforced sidewall with curb and rim guard to provide extra protection against rim and sidewall damage.

## Backhoe Rear- Industrial Plus R-4 XHD Ultra



(R-4B model shown)

| Catalog No. | Size/Ply    | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|-------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 99110-2     | 16.9-24/12  | TBLS | R-4B    | A8           | 16.9                | 51.5                   | 38                       | 7165           | 35.3                |
| 99120-2     | 17.5L-24/12 | TBLS | R-4B    | A8           | 17.5                | 48.9                   | 38                       | 6605           | 32.0                |
| 99130-2     | 19.5L-24/12 | TBLS | R-4B    | A8           | 19.5                | 51.7                   | 33                       | 7605           | 35.9                |
| 99140-2     | 21L-24/12   | TBLS | R-4B    | A8           | 21.0                | 54.3                   | 32                       | 8545           | 36.5                |
| 99160-2     | 14.9-24/12  | TBLS | R-4B    | A8           | 14.9                | 48.9                   | 42                       | 6395           | 32.0                |

### Tire Features & Benefits

- Provides tight center bars for excellent road-ability.
- Reinforced sidewall with curb and rim guard to provide extra protection against rim and sidewall damage.
- Deep tread lugs deliver excellent traction in muddy soil conditions.
- Excellent self cleaning tread design.

## Backhoe Rear- Industrial Ultra R-4 XHD



(R-4 model shown)

| Catalog No. | Size/Ply    | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|-------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 98010L-2    | 16.9-24/12  | TBLS | R-4     | A6           | 16.9                | 51.5                   | 35                       | 5465           | 32.8                |
| 98020L-2    | 17.5L-24/12 | TBLS | R-4     | A6           | 17.5                | 48.9                   | 33                       | 4255           | 33.4                |
| 98030L-2    | 19.5L-24/12 | TBLS | R-4     | A6/*A8       | 19.5                | 51.7                   | 30/*30                   | 4730/*5200     | 37.2                |
| 98040L-2    | 21L-24/12   | TBLS | R-4     | A6/*A8       | 21.0                | 54.3                   | 28/*28                   | 5310/*5840     | 37.2                |

### Tire Features & Benefits

- Wide foot print for high flotation and stability, delivers excellent traction.
- Premium tread width and depth provide increased tire life and trouble-free performance.

## Backhoe Front- Industrial F-3 XHD



(F-3 model shown)

| Catalog No. | Size/Ply  | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|-----------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 19502-2     | 11L-15/14 | TBLS | F-3     | A6           | 11.0                | 32.0                   | 73                       | 2855           | 16.0                |
| 19521-2     | 11L-16/14 | TBLS | F-3     | A6           | 11.0                | 33.0                   | 73                       | 3055           | 16.0                |

### Tire Features & Benefits

- Applicable for agricultural tractors in industrial service and backhoes.
- Deep tread offers excellent impact, cut and puncture resistance.
- Provides superior traction on hard soil, asphalt and concrete.

## Backhoe Front I-3 Bias Tires



(L-2D model shown)

| Catalog No. | Size/Ply      | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|---------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 19532-2     | 10.5/80-18/12 | TBLS | L-2D    | A6           | 10.8                | 34.7                   | 62                       | 3230           | 20.2                |
| 19542-2     | 12.5/80-18/14 | TBLS | L-2D    | A6           | 12.1                | 37.9                   | 62                       | 4675           | 25.2                |
| 19552-2     | 10-16.5/10    | TBLS | L-2D    | A2           | 10.4                | 30.4                   | 75                       | 4710           | 20.2                |
| 19562-2     | 12-16.5/12    | TBLS | L-2D    | A2           | 12.1                | 32.7                   | 80                       | 6320           | 23.9                |

### Tire Features & Benefits

- Applicable for front backhoe service.
- Durable tread pattern for high flotation and super stability.
- Designed to resist chunking and tearing.
- Features also include rim guard and heavy duty sidewall.

## I-3 Trak-Tor Industrial



(R-4C model shown)

| Catalog No. | Size/Ply      | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|---------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 19530-2     | 10.5/80-18/14 | TBLS | R-4C    | A6           | 10.8                | 34.7                   | 70                       | 3375           | 32.0                |
| 19534-2     | 12.5/80-18/16 | TBLS | R-4C    | A6           | 12.1                | 37.9                   | 71                       | 4805           | 32.0                |
| 19536-2     | 10-16.5/12    | TBLS | R-4C    | A2           | 10.4                | 30.4                   | 90                       | 5240           | 21.4                |
| 19537-2     | 12-16.5/14    | TBLS | R-4C    | A2           | 12.1                | 32.7                   | 90                       | 6780           | 26.5                |

### Tire Features & Benefits

- Premium tire for front backhoe service with deeper tread for longer service life.
- Durable tread pattern for high flotation and super stability.
- Designed to resist chunking and tearing.
- Features also include rim guard and heavy duty sidewall.

## Skid Steer- Premium Skid Steer



(L-2D model shown)

| Catalog No. | Size/Ply   | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 16051-2     | 10-16.5/8  | TBLS | L-2D    | A2           | 10.4                | 30.4                   | 59                       | 4140           | 20.2                |
| 16052-2     | 10-16.5/10 | TBLS | L-2D    | A2           | 10.4                | 30.4                   | 75                       | 4710           | 20.2                |
| 16055-2     | 12-16.5/10 | TBLS | L-2D    | A2           | 12.1                | 32.7                   | 65                       | 5600           | 23.9                |
| 16056-2     | 12-16.5/12 | TBLS | L-2D    | A2           | 12.1                | 32.7                   | 80                       | 6320           | 23.9                |
| 16058-2     | 14-17.5/16 | TBLS | L-2D    | A2           | 13.7                | 36.3                   | 100                      | 8260           | 27.7                |
| 16059-2     | 15-19.5/16 | TBLS | L-2D    | A2           | 15.3                | 40.1                   | 80                       | 10880          | 31.5                |

### Tire Features & Benefits

- Applicable for skid-steer and backhoe service.
- Durable tread pattern for high flotation and super stability.
- Designed against resistance to chunking and tearing.
- Features also include rim guard and heavy duty sidewall.

## Skid Steer- Sidewinder Mudder XHD



(L-2E model shown)

| Catalog No. | Size/Ply         | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|------------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 16000-2     | 5.70x12/8        | TBLS | L-2B    | A2           | 5.7                 | 22.4                   | 90                       | 1875           | 18.9                |
| 16002-2     | 23X8.50-12/8     | TBLS | L-2B    | A2           | 8.4                 | 22.6                   | 65                       | 2170           | 18.9                |
| 16004-2     | 27X8.50-15/10    | TBLS | L-2B    | A2           | 8.4                 | 26.7                   | 70                       | 2270           | 18.9                |
| 16050-2     | 10-16.5/8        | TBLS | L-2E    | A2           | 10.4                | 31.4                   | 59                       | 4140           | 21.4                |
| 16054-2     | 10-16.5/10       | TBLS | L-2E    | A2           | 10.4                | 31.4                   | 75                       | 4710           | 21.4                |
| 16028-2     | 10-16.5/12       | TBLS | L-2E    | A2           | 10.4                | 31.4                   | 90                       | 5240           | 21.4                |
| 16030-2     | 10-16.5/14       | TBLS | L-2E    | A2           | 10.4                | 31.4                   | 104                      | 6040           | 21.4                |
| 16038-2     | 12-16.5/14       | TBLS | L-2E    | A2           | 12.4                | 34.1                   | 90                       | 6780           | 26.5                |
| 16040-2     | 12-16.5/16       | TBLS | L-2E    | A2           | 12.4                | 34.1                   | 110                      | 7920           | 26.5                |
| 16042-2     | 33X15.50-16.5/12 | TBLS | L-2E    | A2           | 15.5                | 33.0                   | 61                       | 8005           | 32.1                |

### Tire Features & Benefits

- Ultra heavy duty skid-steer tire.
- Features reinforced sidewalls and rim guard that provides extra protection against sidewall damage.
- Extra deep tread for superior traction and longer tread life.
- Triple step lug provides self cleaning capabilities.

## Skid Steer- Heavy Duty L4A

S = STEEL BELTED N = NYLON BELTED



(L-4A model shown)

| Catalog No. | Size/Ply   | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 16150-2 (S) | 10-16.5/10 | TBLS | L-4A    | A2           | 10.4                | 30.4                   | 75                       | 4710           | 34.0                |
| 16152-2 (S) | 10-16.5/12 | TBLS | L-4A    | A2           | 10.4                | 30.4                   | 90                       | 5240           | 34.0                |
| 16160-2 (S) | 12-16.5/12 | TBLS | L-4A    | A2           | 12.1                | 32.7                   | 80                       | 6320           | 42.2                |
| 16162-2 (S) | 12-16.5/14 | TBLS | L-4A    | A2           | 12.1                | 32.7                   | 90                       | 6780           | 42.2                |
| 16170-2 (S) | 14-17.5/16 | TBLS | L-4A    | A2           | 13.7                | 36.3                   | 100                      | 8260           | 47.2                |
| 16180-2 (S) | 15-19.5/14 | TBLS | L-4A    | A2           | 15.3                | 40.1                   | 70                       | 10060          | 47.2                |
| 16151-2 (N) | 10-16.5/10 | TBLS | L-4A    | A2           | 10.4                | 30.4                   | 75                       | 4710           | 34.0                |
| 16153-2 (N) | 10-16.5/12 | TBLS | L-4A    | A2           | 10.4                | 30.4                   | 90                       | 5240           | 34.0                |
| 16164-2 (N) | 12-16.5/12 | TBLS | L-4A    | A2           | 12.1                | 32.7                   | 80                       | 6320           | 42.2                |
| 16163-2 (N) | 12-16.5/14 | TBLS | L-4A    | A2           | 12.1                | 32.7                   | 90                       | 6780           | 42.2                |
| 16171-2 (N) | 14-17.5/16 | TBLS | L-4A    | A2           | 13.7                | 36.3                   | 100                      | 8260           | 47.2                |
| 16174-2 (N) | 15-19.5/14 | TBLS | L-4A    | A2           | 15.3                | 40.1                   | 70                       | 10060          | 47.2                |

### Tire Features & Benefits

- Severe service skid-steer tire with non-directional design for packed soil, or hard surface applications.
- Reinforced sidewall with curb and rib guard that provides extra protection against rim and sidewall damage.
- Reinforced for superior tread stability and greater penetration resistance.
- Available in steel or nylon belts.

## Farm Front- Harrow-Track F-2



(F-2 model shown)

| Catalog No. | Size/Ply   | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 97100-2     | 4.00-12/4  | TT   | F-2     | A8           | 4.4                 | 21.2                   | 52                       | 495            | 15.1                |
| 97105-2     | 5.00-12/4  | TT   | F-2     | A8           | 5.1                 | 22.4                   | 52                       | 605            | 15.1                |
| 97120-2     | 5.00-15/4  | TT   | F-2     | A8           | 5.1                 | 26.1                   | 44                       | 715            | 16.4                |
| 97125-2     | 7.5L-15/6  | TT   | F-2     | A8           | 8.2                 | 29.4                   | 44                       | 1430           | 18.9                |
| 97130-2     | 9.5L-15/8  | TT   | F-2     | A8           | 9.5                 | 30.8                   | 48                       | 1870           | 30.2                |
| 97135-2     | 11L-15/8   | TT   | F-2     | A8           | 11.0                | 32.0                   | 44                       | 2090           | 34.6                |
| 97140-2     | 5.50-16/4  | TT   | F-2     | A8           | 5.9                 | 28.1                   | 40                       | 860            | 13.9                |
| 97145-2     | 6.00-16/6  | TT   | F-2     | A8           | 6.3                 | 29.1                   | 52                       | 1140           | 18.9                |
| 97150-2     | 6.50-16/6  | TT   | F-2     | A8           | 6.8                 | 30.0                   | 48                       | 1230           | 18.3                |
| 97155-2     | 7.50-16/8  | TT   | F-2     | A8           | 8.0                 | 31.8                   | 56                       | 1710           | 24.6                |
| 97158-2     | 7.50-20/8  | TT   | F-2     | A8           | 8.0                 | 35.8                   | 54                       | 2250           | 26.5                |
| 97160-2     | 10.00-16/8 | TT   | F-2     | A8           | 10.8                | 35.2                   | 44                       | 2340           | 32.8                |
| 97165-2     | 11.00-16/8 | TT   | F-2     | A8           | 12.4                | 38.1                   | 40                       | 2600           | 30.2                |
| 97170-2     | 7.50-18/6  | TT   | F-2     | A8           | 8.0                 | 33.8                   | 44                       | 1610           | 26.5                |
| 97175-2     | 4.00-19/4  | TT   | F-2     | A8           | 4.4                 | 28.2                   | 52                       | 715            | 15.1                |

### Tire Features & Benefits

- All purpose use on farm tractors.
- Three rib design allows for excellent steering capabilities.

## Farm Front- Harrow Track 4 Rib F-2



(F-2A model shown)

| Catalog No. | Size/Ply    | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|-------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 97700-2     | 10.00-16/10 | TT   | F-2A    | A8           | 10.8                | 35.2                   | 52                       | 2600           | 26.5                |
| 97705-2     | 10.00-16/10 | TBLS | F-2A    | A8           | 10.8                | 35.2                   | 52                       | 2600           | 26.5                |
| 97708-2     | 11.00-16-10 | TT   | F-2A    | A8           | 12.4                | 38.1                   | 52                       | 3080           | 29.0                |
| 97710-2     | 11.00-16-12 | TT   | F-2A    | A8           | 12.4                | 38.1                   | 60                       | 3420           | 29.0                |
| 97715-2     | 11.00-16-10 | TBLS | F-2A    | A8           | 12.4                | 38.1                   | 52                       | 3080           | 29.0                |
| 97718-2     | 11.00-16-12 | TBLS | F-2A    | A8           | 12.4                | 38.1                   | 60                       | 3420           | 29.0                |

### Tire Features & Benefits

- Wide foot print and more surface contact allows for even better steering control and resistance to side slip.
- Designed to resist stubble punctures.
- Self cleaning tread design enhanced steering performance.

## Farm Front- Harrow Track I-1



I-1 Model



I-1E Model

| Catalog No. | Size/Ply       | Type | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) |
|-------------|----------------|------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|
| 97180-2     | 8.5L-14/6      | TT   | I-1     | B            | 8.5                 | 28.4                   | 36                       | 1870           | 7.6                 |
| 97185-2     | 9.5L-14/8      | TT   | I-1     | B            | 9.5                 | 29.2                   | 44                       | 2400           | 8.2                 |
| 97190-2     | 11L-14/6       | TT   | I-1     | B            | 11.0                | 29.6                   | 28                       | 2040           | 8.2                 |
| 97195-2     | 5.90-15/4      | TT   | I-1     | B            | 6.1                 | 26.2                   | 36                       | 1140           | 7.6                 |
| 97200-2     | 6.70-15/6      | TT   | I-1     | B            | 6.7                 | 27.7                   | 44                       | 1610           | 7.6                 |
| 97205-2     | 7.60-15/8      | TT   | I-1     | B            | 7.6                 | 28.9                   | 52                       | 2090           | 7.6                 |
| 97206-2     | 7.60-15/8      | TBLS | I-1     | B            | 7.6                 | 28.9                   | 52                       | 2090           | 7.6                 |
| 97210-2     | 9.5L-15/8      | TT   | I-1     | B            | 9.5                 | 30.2                   | 44                       | 2470           | 8.2                 |
| 97212-2     | 9.5L-15/8      | TBLS | I-1     | B            | 9.5                 | 30.2                   | 44                       | 2470           | 8.2                 |
| 97211-2     | 9.5L-15/8      | TT   | I-1E    | B            | 9.8                 | 28.8                   | 44                       | 2470           | 7.6                 |
| 97214-2     | 9.5L-15/8      | TBLS | I-1E    | B            | 9.8                 | 28.8                   | 44                       | 2470           | 7.6                 |
| 97215-2     | 10.00-15/8     | TBLS | I-1     | B            | 10.8                | 33.6                   | 40                       | 3200           | 10.7                |
| 97220-2     | 11L-15/8       | TT   | I-1     | B            | 11.0                | 30.6                   | 36                       | 2540           | 8.2                 |
| 97225-2     | 11L-15/8       | TBLS | I-1     | B            | 11.0                | 30.6                   | 36                       | 2540           | 8.2                 |
| 97219-2     | 11L-15/8       | TT   | I-1E    | B            | 10.9                | 29.4                   | 36                       | 2540           | 7.6                 |
| 97228-2     | 11L-15/8       | TBLS | I-1E    | B            | 10.9                | 29.4                   | 36                       | 2540           | 7.6                 |
| 97230-2     | 12.5L-15/10    | TT   | I-1     | B            | 12.5                | 32.4                   | 44                       | 3000           | 8.8                 |
| 97235-2     | 27X9.50-15/8   | TBLS | I-1     | B            | 9.0                 | 27.0                   | 60                       | 1870           | 12.0                |
| 97240-2     | 6.00-16/6      | TT   | I-1     | B            | 6.3                 | 28.0                   | 44                       | 1520           | 8.2                 |
| 97245-2     | 11L-16/8       | TT   | I-1     | B            | 11.0                | 31.6                   | 36                       | 2680           | 8.2                 |
| 97250-2     | 12.5L-16/10    | TT   | I-1     | B            | 12.5                | 33.4                   | 44                       | 3520           | 8.8                 |
| 97260-2     | 31X13.50-15/10 | TBLS | HF-1    | B            | 13.8                | 30.8                   | 55                       | 2790           | 12.6                |
| 97265-2     | 5.70-15/6      | TT   | I-1     | B            | 5.9                 | 25.7                   | 48                       | 1490           | 8.2                 |

### Tire Features & Benefits

- Outstanding flotation use
- Easy steering from the heavy grooved ribs.
- Extra wide design.
- Non-highway service/ low speed applications.
- Also available in two economy (I-1E) sizes.

## Farm Rear- Agri-Trac R-1+



(R-1KA model shown)

### Tire Features & Benefits

- Bar angle provides superior traction in the field and good wear during road transportation.
- Variety of sizes for use with tractors, combines, and irrigation systems.
- Heavy duty design for excellent ride, snag resistance and long wear.

| Catalog No. | Size/Ply    | Type     | Pattern | Speed Symbol | Section Width (in.) | Overall Diameter (in.) | Inflation Pressure (psi) | Max Load (lbs) | Tread Depth (32nds) | Tread Pattern Pitch |
|-------------|-------------|----------|---------|--------------|---------------------|------------------------|--------------------------|----------------|---------------------|---------------------|
| 97012-2     | 14.9-24/4   | TT       | R-1     | A6/*A8       | 15.0                | 49.8                   | 14/*12                   | 2665/*2200     | 37.8                | 17.0                |
| 97002-2     | 8.3-24/8    | TT       | R-1     | A6           | 8.3                 | 39.2                   | 46                       | 2115           | 35.3                | 19.0                |
| 97003-2     | 9.5-20/8    | TT       | R-1     | A6           | 9.4                 | 37.4                   | 41                       | 2105           | 37.8                | 17.0                |
| 97004-2     | 9.5-24/8    | TT       | R-1     | A6           | 9.4                 | 41.3                   | 41                       | 2445           | 37.8                | 19.0                |
| 96000-2     | 11.2-24/6   | TT       | R-1S    | A6/*A8       | 11.2                | 43.5                   | 26/*26                   | 2300/*2090     | 44.1                | 24.0                |
| 96010-2     | 12.4-24/6   | TT       | R-1S    | A6/*A8       | 12.4                | 45.7                   | 24/*24                   | 2645/*2400     | 45.4                | 24.0                |
| 96015-2     | 14.9-24/8   | TT       | R-1S    | A6/*A8       | 15.0                | 49.8                   | 26/*26                   | 3880/*3520     | 47.9                | 24.0                |
| 96020-2     | 14.9-28/8   | TT       | R-1S    | A6/*A8       | 15.0                | 53.7                   | 26/*26                   | 4145/*3740     | 47.9                | 26.0                |
| 96030-2     | 18.4-38/10  | TT       | R-1S    | A6/*A8       | 18.3                | 69.1                   | 26/*26                   | 6975/*6400     | 51.7                | 30.0                |
| 97000-2     | 11.2-24/4   | TT       | R-1KA   | A6/*A8       | 11.2                | 43.5                   | 19/*18                   | 1860/*1655     | 42.8                | 17.0                |
| 97001-2     | 11.2-24/8   | TT       | R-1KA   | A6           | 11.2                | 43.5                   | 35                       | 2700           | 42.8                | 17.0                |
| 97005-2     | 12.4-24/4   | TT       | R-1KA   | A6/*A8       | 12.4                | 45.7                   | 16/*16                   | 2085/*1870     | 41.6                | 17.0                |
| 97006-2     | 12.4-24/8   | TT       | R-1KA   | A6/*A8       | 12.4                | 49.6                   | 33/*32                   | 3120/*2830     | 41.6                | 19.0                |
| 97010-2     | 14.9-24/6   | TT       | R-1KA   | A6/*A8       | 15.0                | 49.8                   | 20/*20                   | 3330/*3000     | 45.4                | 17.0                |
| 97011-2     | 14.9-24/8   | TT       | R-1KA   | A6/*A8       | 15.0                | 49.8                   | 26/*26                   | 3880/*3520     | 45.4                | 17.0                |
| 97015-2     | 16.9-24/8   | TT       | R-1KA   | A6/*A8       | 16.9                | 52.6                   | 24/*24                   | 4500/*4080     | 49.9                | 17.0                |
| 97020-2     | 18.4-26/6   | TT       | R-1KA   | A6/*A8       | 18.3                | 57.1                   | 16/*16                   | 4385/*3960     | 49.9                | 18.0                |
| 97025-2     | 11.2-28/4   | TT       | R-1KA   | A6/*A8       | 11.2                | 47.4                   | 19/*18                   | 1980/*1760     | 39.1                | 19.0                |
| 97030-2     | 12.4-28/4   | TT       | R-1KA   | A6/*A8       | 12.4                | 49.6                   | 16/*16                   | 2215/*1980     | 41.6                | 19.0                |
| 97035-2     | 13.6-28/6   | TT       | R-1KA   | A6/*A8       | 13.6                | 51.6                   | 23/*22                   | 3155/*2830     | 46.6                | 19.0                |
| 97040-2     | 14.9-28/6   | TT       | R-1KA   | A6/*A8       | 15.0                | 53.7                   | 20/*20                   | 3550/*3200     | 47.9                | 19.0                |
| 97045-2     | 16.9-28/6   | TT       | R-1KA   | A6/*A8       | 16.9                | 56.5                   | 19/*18                   | 4055/*3640     | 49.1                | 19.0                |
| 97050-2     | 16.9-30/6   | TT       | R-1KA   | A6/*A8       | 16.9                | 58.5                   | 19/*18                   | 4190/*3740     | 49.1                | 20.0                |
| 97055-2     | 18.4-30/6   | TT       | R-1KA   | A6/*A8       | 18.3                | 61.0                   | 16/*16                   | 4675/*4190     | 49.9                | 19.0                |
| 97058-2     | 18.4-30/10  | TT       | R-1KA   | A6/*A8       | 18.3                | 61.0                   | 26/*26                   | 6205/*5520     | 49.9                | 19.0                |
| 97057-2     | 24.5-32/10  | TT       | R-1KA   | A6/*A8       | 24.6                | 71.1                   | 20/*20                   | 8710/*7850     | 54.2                | 21.0                |
| 97060-2     | 16.9-34/6   | TT       | R-1KA   | A6/*A8       | 16.9                | 62.4                   | 19/*18                   | 4440/*3960     | 49.1                | 20.0                |
| 97065-2     | 23.1-26/10  | TT       | R-1KA   | A6/*A8       | 23.2                | 63.2                   | 20/*20                   | 7155/*6400     | 52.9                | 19.0                |
| 97066-2     | 18.4-34/8   | TT       | R-1KA   | A6/*A8       | 18.3                | 65.2                   | 20/*20                   | 5655/*5080     | 49.9                | 20.0                |
| 97067-2     | 18.4-34/10  | TT       | R-1KA   | A6           | 18.3                | 65.2                   | 26                       | 6590           | 49.9                | 20.0                |
| 97070-2     | 13.6-38/8   | TT       | R-1KA   | A6           | 13.6                | 61.6                   | 29                       | 4210           | 46.6                | 23.0                |
| 97075-2     | 15.5-38/8   | TT       | R-1KA   | A6           | 15.6                | 61.8                   | 26                       | 4540           | 46.6                | 22.0                |
| 97080-2     | 16.9-38/8   | TT       | R-1KA   | A6/*A8       | 16.9                | 66.3                   | 24/*24                   | 5555/*4940     | 49.1                | 22.0                |
| 97080G-2    | 16.9-38/8   | TT       | R-1     | A6/*A8       | 16.9                | 66.3                   | 24/*24                   | 5555/*4940     | 44.1                | 21.0                |
| 97085-2     | 18.4-38/8   | TT       | R-1KA   | A6/*A8       | 18.3                | 69.1                   | 20/*20                   | 5985/*5360     | 49.9                | 21.0                |
| 97086-2     | 18.4-38/10  | TT       | R-1KA   | A6/*A8       | 18.3                | 69.1                   | 26/*26                   | 6975/*6400     | 49.9                | 21.0                |
| 97090-2     | 20.8-38/8   | TT       | R-1KA   | A6/*A8       | 20.9                | 72.2                   | 19/*18                   | 6810/*6150     | 52.9                | 21.0                |
| 97095-2     | 30.5L-32/16 | Tubeless | R-1C    | A8           | 30.5                | 71.7                   | 26                       | 11000          | 56.7                | 20.0                |
| 97096-2     | 30.5L-32/16 | TT       | R-1C    | A8           | 30.5                | 71.7                   | 26                       | 11000          | 56.7                | 20.0                |

# **SAMSON**

**FARM BACKHOE SKIDSTEER**

Distributed by

